

FA

FORTANO®

The windproof side-mast parasol



#### Unique selling proposition

---

- Unique design language: Harmonises with all giant parasols and F-line
- Continuous mast profile down to the floor covering (internal support tube)
- Patented and synchronous opening mechanism:
  - Operation via crank
  - Simultaneous opening and extension of the parasol roof
  - Opened with just a few turns of the crank
  - High closing height (no need to move the furniture)
- 55 km/h wind stability at size 300 × 300 cm
- Top quality material selection
- Parasol can be rotated by 360° using the turnable base M4
- Osyrion Spot battery-powered LED light with remote
- Anodised natural or anthracite frame ("RAL 7016")

#### Places of use

---

- Small area outdoors



FORTANO®

The windproof side-mast parasol

## Basic model

---

### Frame

- 8 parts made from anodised natural aluminium
- Profiled straight mast
- Mast profile 66 × 95 mm and 3 mm wall thickness
- Roof struts 20 × 26 mm

### Frame material

- Aluminium: EN-AW-6063-T5
- Screws and rivets made from stainless steel A2
- Anodisation:
  - Profile surface finishing
  - High degree of hardness – wear resistance (“scratch-resistant”)
  - Increased corrosion resistance
  - Natural appearance (adaptation to environment)
  - Modern look (luxurious matt)

### Frame colour

- Anodised natural matt or anthracite (“RAL 7016”) powder-coated

### Opening principle (synchronous)

- Patented opening mechanism for high closing height
- Fast and simple operation thanks to synchronous opening and extension of the parasol roof
- Opened with just a few turns of the crank

### Drive

- With hand crank

### Canopy

- Without flounce
- Self-tautening thanks to the flexible strut ends
- Available in 3 fabric qualities:
  - 100 % polyacrylic approx. 300 g/m<sup>2</sup> (spun dyed)
  - 100 % polyester approx. 250 g/m<sup>2</sup> (spun dyed)
  - 100 % polyester approx. 220 g/m<sup>2</sup> (piece dyed)
- Replaceable or interchangeable canopies

### Wind stability

- Up to 55 km/h (with fixed anchorage)
- Tested in a wind tunnel

## Fixations

---

[More information](#)

- Bases / parasol stands / covers
- Ground sockets
- Mounting plates without or with installation height made to measure
- Mounting plates for insulation floors
- Mounting plates for insulation floors with high insulation
- Base plates made to measure

## Additional options – Standard accessories

---

[More information](#)


- Turnable base M4 for 360° rotation
- Osyrion Spot battery-powered LED light, removable
- Protective cover

## Special product solutions – Made to measure


---

[More information](#)

- Glatz Green® Special fabric
- Special fabrics (third-party fabrics, flame retardant)
- Printing & advertising print



Loose cover max. 10 cm, concrete thickness  
min. 30 cm (pay attention to frost depth), Guarantee  
water drainage



Nominal size	Lateral distance	Pole Ø	Area covered	Crank handle height	Height closed	Clear headroom	Total height/open	Height of pole	Overhang at the back	Length of free-arm	Foundation	Minimum weight for base	max. wind speed open perm.
cm	cm	cm	m²	cm	cm	cm	cm	cm	cm	cm	cm	kg	km/h (wind force)
<b>A</b>	<b>AS</b>	<b>M¹</b>	<b>B</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G¹/G²</b>	<b>M²</b>	<b>N</b>	<b>Z</b>	<b>C</b>		
300 × 300	-	6.6 × 9.5	9	106	105	215	320/270	265	12	175	60 × 60	180	55 (7)
400 × 300	-	6.6 × 9.5	12	106	65	215	320/270	265	12	175	60 × 60	180	45 (6)

The listed measures represent extrapolated average values that may be slightly different on the product ( $\pm 2\% \pm 5$  cm).

The height dimensions are based on the ground socket M4. With the base M4, 120 kg these vary by plus 11.5 cm and with the base M4, 180 kg by plus 15.5 cm.

The lowest height for opening/closing is 5 cm below the closing height.

The max. wind speed limits as per our separate sheet apply only if the parasol canopy is in a horizontal position and if there is a fix ground anchorage. A base with the specified minimum weight is not sufficient.

In the presence of several parasols, the minimum distance between one parasol and another and between parasols and walls shall be 20 cm.



1



2



3



4



5

Glatz AG

+41 52 723 66 44  
contract@glatz.com  
glatz.com

